

ROLLANT		455 RC UNIWRAP	455 RC	454 RC UNIWRAP	454 RC
Hitching					
PTO shaft speed	rpm	1000	1000	1000	1000
Power requirement	kW/hp	107/145	74/100	107/145	74/100
Ball hitch		○	○	○	○
Drive chains		Heavy duty	Heavy Duty	Heavy Duty	Heavy Duty
Hydraulic connection					
2 x single-acting spool valve and open return line		●	●	●	●
Pick-up					
Width	m	2.10	2.10	2.10	2.10
DIN raking width	m	1.90	1.90	1.90	1.90
Roller crop press		○	○	○	○
Oscillating pick-up castor gauge wheels		●	●	●	●
Crop feed					
ROTO CUT Heavy Duty chopping rotor		●	●	●	●
Number of knives		25 (0, 12, 13, 25)	25 (0, 12, 13, 25)	25 (0, 12, 13, 25)	25 (0, 12, 13, 25)
HD knives		○	○	○	○
Blanked-off knives		○	○	○	○
Lowerable PRO cutting floor		●	●	●	●
Bale chamber					
Number of compaction rollers		16	16	16	16
Automatic chain lubrication		●	●	●	●
Automatic central lubrication for baler bearings		○	○	○	○
Bale ejector		–	●	–	●
Bale chamber dimensions					
Width	m	1.20	1.20	1.20	1.20
Diameter	m	1.25–1.35	1.25–1.35	1.25–1.35	1.25–1.35
Operation					
COMMUNICATOR II		●	●	●	●
CLAAS MEDIUM TERMINAL II (wrapper)		●	–	●	–
OPERATOR		–	–	–	–
ISOBUS cable		●	●	●	●
Wrapping and tying					
Net wrapping		●	●	●	●
Twine tying		–	–	–	–
Wrapper					
Film stretcher	mm	2 × 750	–	2 × 750	–
Film capacity		14 rolls	–	14 rolls	–
Overlap, configurable	%	52	–	52	–
Pre-stretching	%	67 (82 ○)	–	67 (82 ○)	–
Slope equipment		○	–	–	–
Tyres					
15.0/55-17 10PR		–	●	–	●
19.0/45-17 10PR		–	○	–	○
550/60-22.5		●	–	●	–
560/45-22.5 16PR		–	○	–	○
620/55 R 26.5		○	–	○	–
Air brakes		●	○	●	○
Overall dimensions					
Length	m	6990	4250	6990	4250
Width	m	2955	2955	2955	2955
Height	m	3250	3250	3250	3250
Weight	kg	5800	3150	5800	3150
Options					
Work lights		○	○	○	○
Bale twister		○	○	○	○
Load sensing		○	○	○	○

ROLLANT		375 RC UNIWRAP	375 RC	374 RC	374 RF
Hitching					
PTO shaft speed	rpm	1000	1000	1000	1000
Power requirement	kW/hp	88/120	68/92	68/92	68/92
Drive chains		Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty
Hydraulic connection					
One-way spool valve for pick-up lift and dual-acting spool valve for tailgate rams		–	●	●	●
Single-acting spool valve and open return line		●	–	–	–
Pick-up					
Width	m	2.10	2.10	2.10	2.10
DIN raking width	m	1.90	1.90	1.90	1.90
Roller crop press		○	○	○	○
Oscillating pick-up castor guide wheels		●	●	●	●
Crop feed					
ROTO CUT Heavy Duty chopping rotor		●	●	●	–
Number of knives		16	16	16	–
Lowerable PRO cutting floor		●	●	●	–
Bale chamber					
Number of compaction rollers		16	16	16	16
Automatic chain lubrication		●	●	●	●
Automatic central lubrication for baler bearings		○	○	○	○
Bale ejector		–	●	●	●
Bale chamber dimensions					
Width	m	1.20	1.20	1.20	1.20
Diameter	m	1.25	1.25	1.25	1.25
Operation					
COMMUNICATOR II		●	–	–	–
CLAAS MEDIUM TERMINAL II (wrapper)		●	–	–	–
OPERATOR		–	●	●	●
ISOBUS cable		●	●	●	●
Wrapping and tying					
Net wrapping		●	●	●	●
Twine tying		●	●	●	●
Wrapper					
Film stretcher	mm	2 × 750	–	–	–
Film capacity		12 rolls	–	–	–
Overlap, configurable	%	52	–	–	–
Pre-stretching	%	67 (82 ○)	–	–	–
Tyres					
15.0/55-17 10PR		–	●	●	●
19.0/45-17 10PR		–	○	○	○
500/45-22.5 12PR		–	○	○	○
560/45-22.5 12PR		●	–	–	–
Air brakes		●	○	○	○
Overall dimensions					
Length	mm	6690	4720	4720	4720
Width	mm	2980	2330–2770	2330–2770	2330–2770
Height	mm	2830	2310	2310	2310
Weight	kg	4700	2750	2750	2750

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.

● Standard ○ Optional □ Available – Not available