

Front attachment matrix - cutterbars

Front attachment matrix - cutterbars

	LEXION 8000			LEXION 7000				LEXION 6000				LEXION 5000		
	8900	8800	8700	7700	7600	7500	7400	6900	6800	6700	6600	5500	5400	5300
CERIO cutterbars														
CERIO 930	■	■	■	■	■	■	■	■	■	■	■	■	■	■
CERIO 770	■	■	■	■	■	■	■	■	■	■	■	■	■	■
CERIO 680	■	■	■	■	■	■	■	■	■	■	■	■	■	■
CERIO 620	—	—	—	■	■	■	■	■	■	■	■	■	■	■
CERIO 560	—	—	—	■	■	■	■	■	■	■	■	■	■	■
Standard cutterbars														
C 490	—	—	—	—	—	—	—	—	—	—	—	—	—	—
C 450	—	—	—	—	—	—	—	—	—	—	—	—	—	—
C 430	—	—	—	—	—	—	—	—	—	—	—	—	—	—
C 420	—	—	—	—	—	—	—	—	—	—	—	—	—	—
C 370	—	—	—	—	—	—	—	—	—	—	—	—	—	—
VARIO cutterbars														
VARIO 1380	■ ¹	■ ¹	—	—	—	—	—	—	—	—	—	—	—	—
VARIO 1230	■	■	■	■	■	■	■	■ ¹	■ ¹	■ ¹	—	—	—	—
VARIO 1080	■	■	■	■	■	■	■	■	■	■	■	—	—	—
VARIO 930	■	■	■	■	■	■	■	■	■	■	■	■	■	■
VARIO 770	■	■	■	■	■	■	■	■	■	■	■	■	■	■
VARIO 680	■	■	■	■	■	■	■	■	■	■	■	■	■	■
VARIO 620	—	—	—	■	■	■	■	■	■	■	■	■	■	■
VARIO 560	—	—	—	—	—	—	—	■	■	■	■	■	■	■
VARIO 500	—	—	—	—	—	—	—	■	■	■	■	■	■	■
MAXFLEX cutterbars														
MAXFLEX 930	■	■	■	■	■	■	■	■	■	■	■	■	■	■
MAXFLEX 770	■	■	■	■	■	■	■	■	■	■	■	■	■	■
MAXFLEX 680	—	—	—	—	—	—	—	■	■	■	■	■	■	■
MAXFLEX 620	—	—	—	—	—	—	—	■	■	■	■	■	■	■
MAXFLEX 560	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CONVIO FLEX cutterbars														
CONVIO FLEX 1380	■	■	—	—	—	—	—	■ ¹	■ ¹	—	—	—	—	—
CONVIO FLEX 1230	■	■	■	■	■	■	■	■ ¹	■ ¹	■ ¹	—	—	—	—
CONVIO FLEX 1080	■	■	■	■	■	■	■	■	■	■	■	—	—	—
CONVIO FLEX 930	■	■	■	■	■	■	■	■	■	■	■	—	—	—
CONVIO FLEX 770	■	■	■	■	■	■	■	■	■	■	■	■	■	■
CONVIO cutterbars														
CONVIO 1380	■	■	■	■	■	■	■	■ ¹	■ ¹	—	—	—	—	—
CONVIO 1230	■	■	■	■	■	■	■	■ ¹	■ ¹	■ ¹	—	—	—	—
CONVIO 1080	■	■	■	■	■	■	■	■	■	■	■	—	—	—
CONVIO 930	■	■	■	■	■	■	■	■	■	■	■	—	—	—
CONVIO 770	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Folding cutterbars														
C 540	—	—	—	■	■	■	■	■	■	■	■	■	■	■
C 450	—	—	—	—	—	—	—	■	■	■	■	■	■	■

■ Recommended □ Not recommended – Not available

¹ TERRA TRAC only

Please note that these recommendations are not valid for all regions. The regional road traffic regulations must be observed. The front attachment matrix may vary as a result of differing climatic conditions or cultivation methods.

The availability of individual combine harvester models depends on the applicable emissions standard for the country concerned and can therefore vary subject to national regulation.

Front attachment matrix - pickers.

Front attachment matrix - pickers

	LEXION 8000			LEXION 7000				LEXION 6000				LEXION 5000		
Front attachment	8900	8800	8700	7700	7600	7500	7400	6900	6800	6700	6600	5500	5400	5300
CORIO 12-row														
CORIO 1275 C CONSPEED	■	■	■	■	■	■	■	■	■	■	■ ¹	—	—	—
CORIO 1270 C CONSPEED	■	■	■	■	■	■	■	■	■	■	■ ¹	—	—	—
CORIO 8-row unit														
CORIO 890 CONSPEED	■	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 880 FC CONSPEED	■	■	■	■	■	■	■	■	■	■	■	—	—	—
CORIO 880 FC	■	■	■	■	■	■	■	■	■	■	■	—	—	—
CORIO 875 C CONSPEED	■	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 875 FC CONSPEED	■	■	■	■	■	■	■	■	■	■	■	—	—	—
CORIO 875 C	■	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 875 FC	■	■	■	■	■	■	■	■	■	■	■	—	—	—
CORIO 870 C CONSPEED	■	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 870 FC CONSPEED	■	■	■	■	■	■	■	■	■	■	■	—	—	—
CORIO 870 C	■	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 870 FC	■	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 6-row unit														
CORIO 690 CONSPEED	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CORIO 680 FC CONSPEED	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CORIO 680 FC	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CORIO 675 C CONSPEED	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CORIO 675 FC CONSPEED	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CORIO 675 C	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CORIO 675 FC	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CORIO 670 C CONSPEED	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CORIO 670 FC CONSPEED	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CORIO 670 C	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CORIO 670 FC	—	—	—	—	—	—	—	■	■	■	■	■	■	■
CORIO 5-row unit														
CORIO 575 C	—	—	—	—	—	—	—	—	—	—	—	—	—	—
CORIO 570 C	—	—	—	—	—	—	—	—	—	—	—	—	—	—
CORIO 4-row unit														
CORIO 475 C	—	—	—	—	—	—	—	—	—	—	—	—	—	—
CORIO 470 C	—	—	—	—	—	—	—	—	—	—	—	—	—	—
CORIO 475 C (DOMINATOR only)	—	—	—	—	—	—	—	—	—	—	—	—	—	—
CORIO 470 C (DOMINATOR only)	—	—	—	—	—	—	—	—	—	—	—	—	—	—
SWATH UP														
SWATH UP 450	■	■	■	■	■	■	■	■	■	■	■	■	■	■
SUNSPEED														
SUNSPEED 16-70	■	■	■	■	■	■	■	■	■	■	■	—	—	—
SUNSPEED 12-75	■	■	■	■	■	■	■	■	■	■	■	■	■	■
SUNSPEED 12-70	■	■	■	■	■	■	■	■	■	■	■	■	■	■
SUNSPEED 8-75	—	—	—	—	—	—	—	—	—	—	—	—	—	—
SUNSPEED	—	—	—	—	—	—	—	—	—	—	—	—	—	—
8-70	—	—	—	—	—	—	—	—	—	—	—	—	—	—

■ Recommended □ Not recommended — Not available

¹ TERRA TRAC only

	TUCANO 500				TUCANO 400				TUCANO 300		AVERO		DOMINATOR
Front attachment	580	570	560	550	450	440	430	420	340	320	240	160	130
CORIO 12-row													
CORIO 1275 C CONSPEED	—	—	—	—	—	—	—	—	—	—	—	—	—
CORIO 1270 C CONSPEED	—	—	—	—	—	—	—	—	—	—	—	—	—
CORIO 8-row unit													
CORIO 890 CONSPEED	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 880 FC CONSPEED	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 880 FC	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 875 C CONSPEED	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 875 FC CONSPEED	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 875 C	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 875 FC	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 870 C CONSPEED	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 870 FC CONSPEED	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 870 C	■	■	■	■	■	■	■	■	■	■	■	■	■
CORIO 870 FC	■	■											

Front attachments		CONVIO FLEX / CONVIO cutterbars						VARIO cutterbars						CERIO cutterbars						Standard cutterbars					Folding cutterbars					
		1380	1230	1080	930	770		1380	1230	1080	930	770	680	620	560	500	930	770	680	620	560	C 490	C 450 ¹	C 430	C 420 ¹	C 370	C 540	C 450		
Effective cutting width	mm	13868	12344	10820	9296	7772	13790	12270	10740	9220	7696	6781	6172	5562	4953	9220	7696	6781	6172	5562	4920	4550	4320	4240	3710	5460	4550			
Effective cutting width	ft.	45.50	40.50	35.50	30.50	25.50	45.25	40.25	35.25	30.25	25.25	22.25	20.25	18.25	16.25	30.25	25.25	22.25	20.25	18.25	16.14	14.93	14.17	13.91	12.17	17.91	14.93			
Drive on both sides		●	●	●	○	—	●	●	●	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	●	●			
Drive on one side		—	—	—	○	●	—	—	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	—	—		
Grain crop divider, folding		○	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
Crop dividers adjustable for height without tools		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	—	—		
Soybean crop divider		○	○	○	○	○	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—		
Spacing of knife bar to intake auger (min. / max)	mm	—	—	—	—	—	493/1134	493/1134	493/1134	493/1134	493/1134	493/1134	493/1134	493/1134	493/1134	493/1134	493/1134	493/1134	493/1134	579	579	579	579	545	560	560	580	545	560	560
Knife divided		●	●	●	○	—	●	●	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	●	●		
Knife undivided		—	—	—	●	●	—	—	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
MULTIFINGER intake auger		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
Reel and auger bearing divided		●	●	●	●	—	●	●	●	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	●	●			
Reel and auger bearing undivided		—	—	—	●	●	—	—	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
Crop lifters		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
Vertical flexibility of knife bar	mm	225/—	225/—	225/—	225/—	225/—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—		
ACTIVE FLOAT		●/-	●/-	●/-	●/-	●/-	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—		
Intake auger diameter (ext. / int.)		660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	660/420	580/380	580/380	580/380	580/380	580/380	580/380	580/380			
Replacement knife		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
possible adjustment range, hydraulic	mm	—	—	—	—	—	700	700	700	700	700	700	700	700	700	700	—	—	—	—	—	—	—	—	—	—	—	—		
possible adjustment range, manual	mm	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	200	200	200	200	200	—	—	—	—	—	—		
Side belt depth	mm	1079.5	1079.5	1079.5	1079.5	1079.5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—		
Trough depth	mm	1329	1329	1329	1329	1329	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—		
Width of centre belt	mm	2000	2000	2000	2000	2000	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—		
Weight (without rapeseed equipment)	kg	4600/4550	4350/4300	4050/4000	3510/3425	3000/2935	4435	4055	3665	2989	2557	2334	2224	2093	1941	2824	2419	2140	2040	1926	1300	1080	1120	1000	940	2100	1980			

ments		930	770	MAXFLEX cutterbars	680	620	560
ng width	mm	9220	7696	6781	6172	5563	
ng width	ft.	30.25	25.25	22.25	20.25	18.25	
sides	–	–	–	–	–	–	
side	●	●	●	●	●	●	
ility of knife bar	mm	180	180	180	180	180	
	–	–	–	–	–	–	
ed	●	●	●	●	●	●	
intake auger	●	●	●	●	●	●	
er bearing divided	–	–	–	–	–	–	
er bearing undivided	●	●	●	●	●	●	
	○	○	○	○	○	○	
knife	●	●	●	●	●	●	
ves	–	–	–	–	–	–	
d augers	–	–	–	–	–	–	
	kg	2670	2290	1960	1890	1770	
cutterbar control							
UR	○	○	○	○	○	○	
Working position	●	●	●	●	●	●	
erating position	●	●	●	●	●	●	
control	●	●	●	●	●	●	
el height	●	●	●	●	●	●	
el levelling	–	–	–	–	–	–	
	○	○	○	○	○	○	

Dimensions		SWATH UP 450	Front attachments		SUNSPEED				
			16-70	12-75	12-70	8-75	8-70		
Up width	mm	4523	Number of rows		16	12	12	8	8
Up width	ft.	14.84	Row width	cm	70	75	70	75	70
side		•	Shuttle length	mm	1800	1800	1800	1800	1800
o fingers		392	Shuttle width	mm	311	337	311	337	311
	kg	1366	Shuttle gap adjustment range	mm	30-50	30-50	30-50	30-50	30-50
Reel and auger bearing			undivided		—	—	•	•	•
			divided		•	—	—	—	—
reel: undivided, auger: divided				—	•	—	—	—	—
Replacement knife				•	•	•	•	•	•
Weight		kg	3300	2820	2638	1800	1720		
Automated cutterbar control									
Reel speed control			•	•	•	•	•	•	•
Automatic reel height			•	•	•	•	•	•	•
Automatic reel levelling			—	—	—	—	—	—	—

ually develops its products to meet customers' requirements, all products are subject to change without notice. All descriptions and specifications in this brochure should be considered and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please consult your nearest CLAAS dealer and their price specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid hazards, never remove these protective panels refer to the relevant instructions in the operator's manual in this regard.

Specifications relating to engines are based on the European emission regulation standards: Stage. Any reference to the Tier standards in this document is intended solely for information ease of understanding. It does not imply approval for regions in which emissions are regulated by Tier.

DOMINATORB only

Front attachments	CORIO CONSPEED 12-row		CORIO CONSPEED 8-row						CORIO CONSPEED 6-row						CORIO 8-row				CORIO 6-row				CORIO 5-row		CORIO 4-row						
	1275 C	1270 C	890	880 FC	875 C	875 FC	870 C	870 FC	690	680 FC	675 C	675 FC	670 C	670 FC	880 FC	875 C	875 FC	870 C	870 FC	680 FC	675 C	675 FC	670 C	670 FC	575 C	570 C	475 C	470 C	475 C ¹	470 C ¹	
Number of rows	12	12	8	8	8	8	8	8	6	6	6	6	6	6	8	8	8	8	6	6	6	6	6	6	5	5	4	4	4	4	
Row width	cm	75	70	90	80	75	75	70	70	90	80	75	75	70	70	80	75	75	70	80	75	75	70	70	75	70	75	70	70		
Transport position – rigid		●	●	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	●	●	●	●	●	●	
Transport position – folding		–	–	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	–	–	–	–	–	–	–
Horizontal chopper		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Working width	m	9.78	8.63	7.17	6.53	6.18	6.18	5.83	5.83	5.37	4.93	4.68	4.68	4.43	4.43	6.53	6.18	6.18	5.83	5.83	4.93	4.68	4.68	4.43	4.43	3.93	3.73	3.18	3.03	3.18	3.03
Transport width	m	9.78	8.63	7.17	3.35	6.18	3.00	5.83	3.00	5.37	3.35	4.68	3.00	4.43	3.00	3.35	6.18	3.00	5.83	3.00	3.35	4.68	3.00	4.43	3.00	3.93	3.73	3.18	3.03	3.18	3.03
Stubble breaker		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
MONTANA mounting kit		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Sunflower kit		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Hood extensions		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Laid maize augers		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Shear bar kit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Sprocket for intake auger speed increase		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Electrohydraulic snapping plate adjustment		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Intake auger loss protection		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Road transport protection incl. lighting and safety bar		–	–	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	–	–	–	–	–	–	–
Support for trailer		○	○	○	–	○	–	○	–	○	–	○	–	○	–	○	–	○	–	○	–	○	–	○	–	○	○	○	○	○	○
Weight	kg	3820	3700	3750	2990	2590	2910	2510	2855	2150	2355	2030	2295	2030	2295	3110	270	3030	2630	2950	2445	2120	2385	2120	2385	1770	1770	1475	1475	1460	1460

Automated cutterbar control

AUTO CONTOUR	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
AUTO PILOT	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

¹ For DOMINATOR 130 only